

1. PRODUCT AND COMPANY IDENTIFICATION

MANUFACTURER: Davis Instrument Corp.
3465 Diablo Avenue,
Hayward, CA 94545
(510)732-9229

PRODUCT PART NO & NAME: #730 Slick Seam

CHECMICAL NAME &
SYNONYM N/A

CHEMICAL FAMILY : Petrolatum & Microcrystalline Wax NF

FORMULA : Proprietary

2. HAZARDS IDENTIFICATION

Physical state	Soft	HMIS:	
Color	Greenish - brown	Health :	0
Odor	Odorless	Flammability :	1
		Physical Hazard :	0
		Personal Protection	See SDS section 8

DANGER



Hazard Statement :

May be harmful if swallowed.

Precautionary Statement:

Keep container tightly closed. Store away from flame, heat, Sparks, Open flame, food, drink and smoking material. Wear safety glass. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present. Continues rinsing. If molten slick Seam contact skin, flush immediately with cold water. Call a physician. For solidified slick Seam, remove excess with paper towel, wash with soap and water.

=====

3. COMPOSITION / INFORMATION ON INGREDIENTS

=====

DESCRIPTION	CAS#	%	TLV	Unit
Silica	14808-60-7	1		
Magnesium Silicate Hydrate	14707-96-6	19		
Titanium Dioxide	13463-67-3	0.002		
Yell Proto		37		
Microcrystalline wax		37		

=====

4. FIRST AID MEASURES

=====

Threshold limit Value: None established.

Eye contact : Flush immediately with cold water. Call a physician .
Skin contact: For molten slick Seam, flush immediately with cold water. Call a physician. For solidified slick Seam, remove excess with paper towel, wash with soap and water..
Ingestion: Call a physician.
Inhalation: None.

=====

5. FIRE-FLIGHTING MEASURE

=====

Flash point: >204°C / > 410°F (ASTM D-92)
Flammable Limits: LEL: N/A UEL: N/A
Extinguishing Media: Dry Chemical, foam, CO₂ , Water fog, Sand/Earth
Special Fire Fighting Procedure: Water spray is an unsuitable extinguish agent. Firefighters should use self-contained breathing apparatus to protect against smoking inhalation.
Unusual Fire and Explosion hazards: none

=====

6. ACCIDENTAL RELEASE MEASURES

=====

Shut off leak and dike up large spills. After cooling and solidification, scrape , and /or shovel up material. Finally, clean area with oil absorbent material.

7. HANDLING AND STORAGE

Store away from flame, heat (250°F max) , and strong oxidizing agents. Avoid skin and eye contact.

8. EXPOSURE CONTROL / PERSONAL PROTECTION

Respiratory protection: N/A

Ventilation: N/A.

Protective Gloves: When molten, wear imperious gloves.

Eye Protection: when molten, wear a face shield over safety glasses.

Other Protective Equipment: When molten , wear coveralls.



9. PHYSICAL AND CHEMICAL PROPERTIES

Boiling Point :	N/A
Specific Gravity (H ₂ O) :	0.815 – 0.89 @ 60°F
Vapor Pressure (mmHg):	N/A
Vapor Density (Air=1):	N/A
Evaporation Rate (H ₂ O) :	N/A
Solubility in Water:	Nil
pH:	N/A
Appearance and Odor	Soft, greenish-brown, non-aromatic wax

10. STABILITY AND REACTIVITY

Stability: Stable

Incompatibility: Keep away from flame, heat (250°F max) , and strong oxidizing agents

Hazardous Decomposition Upon combustion, carbon monoxide and carbon dioxide are generated.

Hazardous Polymerization : None

=====

11. TOXICOLOGICAL INFORMATION

=====

Inhalation: N/A
Ingestion : Harmful if swallowed
Skin contact : No known significant effects or critical hazards.
Eye contact: No known significant effects or critical hazards.

=====

12. ECOLOGICAL INFORMATION

=====

Ecological information : Not known

=====

13. DISPOSAL CONSIDERATIONS

=====

Recommended method of disposal: Dispose according to current local, State and Federal regulations.
Hazardous waste number: Not a RCRA hazardous waste.

=====

14. TRANSPORT INFORMATION

=====

General: Not regulated.

=====

15. REGULATORY INFORMATION

=====

Not regulated.

=====

16. OTHER INFORMATION

=====

Not Available

- End-